

DUAL CAMERA SURVEILLANCE AND CONTROL SYSTEM

CLAIMS

I Claim:

1. A dual camera surveillance and control system comprising:
 - a) a color camera for observation under bright daytime conditions;
 - b) a monochrome camera for observation under infrared illumination for dark night-time conditions;
 - c) an infrared illuminator;
 - d) a control module for selection of color or monochrome camera operation and of infrared illumination, depending on ambient light conditions.
2. The dual camera surveillance and control system of Claim 1, in which the color camera has a lens optimized for color with infra-red filtering.
3. The dual camera surveillance and control system of Claim 1, in which the monochrome

camera has a lens optimized for monochrome viewing.

4. The dual camera surveillance and control system of Claim 1, in which the monochrome camera is supercharged for infrared sensitivity.

5. The dual camera surveillance and control system of Claim 1, in which the infra-red illuminator gives illumination in the range of from 805 to 995 nanometers of electromagnetic radiation.

6. The dual camera surveillance and control system of Claim 1, in which the color camera and the monochrome camera each has an independent lens having a separate variable focal control via the control module, providing a switch of mode from daylight to infrared night-light operation without a focal shift.

7. The dual camera surveillance and control system of Claim 1, comprising an auto iris control board that independently controls an iris in each independent lens.

8. The dual camera surveillance and control system of claim 1, in which a video output signal is switched from mono to color depending on the ambient light levels.

9. The dual camera surveillance and control system of Claim 2, in which

a) the monochrome camera has a lens optimized for monochrome viewing;

- b) the monochrome camera is supercharged for infrared sensitivity;
- c) the infra-red illuminator gives illumination in the range of from 805 to 995 nanometers of electromagnetic radiation;
- d) the color camera and the monochrome camera each have an independent lens having a separate variable focal control via the control module, providing a switch of mode from day to night operation without a focal shift.
- e) an auto iris control board that independently controls an iris in each independent lens.
- f) a video output signal is switched from mono to color depending on the ambient light levels.

10. The dual camera surveillance and control system of Claim 1, comprising:

- a) a power system having a battery, an energy management module, and an ambient energy charger for the battery;
- b) a low power detection module;
- c) a wireless transmitter for transmission of video to a base.

11. [amended re antecedent as per Examiner requirement] The dual camera surveillance and control system of Claim 10, further comprising a wireless receiver for receiving instructions for the dual camera surveillance and control system from the base.

12. The dual camera surveillance and control system of Claim 10, in which the energy management module comprises a day/night sensor and a power select switch and in which the ambient energy charger is a solar panel that converts solar energy to electrical current.

13. The dual camera surveillance and control system of Claim 10, further comprising a communications board to intelligently capture desired relevant video data at a remote location for transmission to another location.

14. [amended re indefiniteness as per Examiner requirement] The dual camera surveillance and control system of Claim 10, further comprising an internet protocol module by which users control the surveillance camera at a remote location over the internet.

15. The dual camera surveillance and control system of Claim 10, further comprising a satellite based video data transfer module.

16. [amended re antecedent as per Examiner requirement] The dual camera surveillance and control system of Claim 10, further comprising a housing that is weather-tight.

17. [amended re indefiniteness and antecedent as per Examiner requirement] The dual camera surveillance and control system of Claim 10, in which the energy management module comprises a day/night sensor and a power select switch and in which the ambient energy charger is a solar panel that converts solar energy to electrical current, and further comprising:

- a) a communications board to intelligently capture desired relevant video data at a remote location for transmission to another location;
- b) an internet protocol module by which users control the surveillance camera at a remote location;
- c) a satellite based video data transfer module;
- d) a housing that is weather-tight.

18. [amended re antecedent and indefiniteness as per Examiner requirement] The dual camera surveillance and control system of Claim 9, comprising:

- a) a power system having a battery, an energy management module, and an ambient energy charger for the battery, in which the energy management module comprises a day/night sensor, a low power detection module and a power select switch, and in which the ambient energy charger is a solar panel that converts solar energy to electrical current;

- b) a wireless transceiver for transmission of video to a base and for receiving instructions for the dual camera surveillance and control system from the base;
- c) a communications board to intelligently capture desired relevant video data at a remote location for transmission to another location;
- d) an internet protocol module by which users control the surveillance camera at a remote location over the internet;
- e) a satellite based video data transfer module;
- f) a housing for the components that is weather-tight.

19. [amended re antecedent as per Examiner requirement] The dual camera surveillance and control system of Claim 10, further comprising a housing that is a weather-tight, substantially spherical dome having flat windows, the color camera and the mono camera mounted on a central axis within the sphere to allow pan and tilt rotation in full 360 degree rotation on two axes.

[MARKED - UP COPY]

DUAL CAMERA SURVEILLANCE AND CONTROL SYSTEM

CLAIMS

I Claim:

1. A dual camera surveillance and control system comprising:
 - a) a color camera for observation under bright daytime conditions;
 - b) a monochrome camera for observation under infrared illumination for dark night-time conditions;
 - c) an infrared illuminator;
 - d) a control module for selection of color or monochrome camera operation and of infrared illumination, depending on ambient light conditions.
2. The dual camera surveillance and control system of Claim 1, in which the color camera has a lens optimized for color with infra-red filtering.
3. The dual camera surveillance and control system of Claim 1, in which the monochrome

camera has a lens optimized for monochrome viewing.

4. The dual camera surveillance and control system of Claim 1, in which the monochrome camera is supercharged for infrared sensitivity.

5. The dual camera surveillance and control system of Claim 1, in which the infra-red illuminator gives illumination in the range of from 805 to 995 nanometers of electromagnetic radiation.

6. The dual camera surveillance and control system of Claim 1, in which the color camera and the monochrome camera each has an independent lens having a separate variable focal control via the control module, providing a switch of mode from daylight to infrared night-light operation without a focal shift.

7. The dual camera surveillance and control system of Claim 1, comprising an auto iris control board that independently controls an iris in each independent lens.

8. The dual camera surveillance and control system of claim 1, in which a video output signal is switched from mono to color depending on the ambient light levels.

9. The dual camera surveillance and control system of Claim 2, in which

a) the monochrome camera has a lens optimized for monochrome viewing;

- b) the monochrome camera is supercharged for infrared sensitivity;
- c) the infra-red illuminator gives illumination in the range of from 805 to 995 nanometers of electromagnetic radiation;
- d) the color camera and the monochrome camera each have an independent lens having a separate variable focal control via the control module, providing a switch of mode from day to night operation without a focal shift.
- e) an auto iris control board that independently controls an iris in each independent lens.
- f) a video output signal is switched from mono to color depending on the ambient light levels.

10. The dual camera surveillance and control system of Claim 1, comprising:

- a) a power system having a battery, an energy management module, and an ambient energy charger for the battery;
- b) a low power detection module;
- c) a wireless transmitter for transmission of video to a base.

11. The dual camera surveillance and control system of Claim 10, further comprising a wireless receiver for receiving instructions for the ~~system~~ *dual camera surveillance and control* from the base.

12. The dual camera surveillance and control system of Claim 10, in which the energy management module comprises a day/night sensor and a power select switch and in which the ambient energy charger is a solar panel that converts solar energy to electrical current.

13. The dual camera surveillance and control system of Claim 10, further comprising a communications board to intelligently capture desired relevant video data at a remote location for transmission to another location.

14. The dual camera surveillance and control system of Claim 10, further comprising an internet protocol module by which users ~~can control~~ the surveillance camera at a remote location over the internet.

15. The dual camera surveillance and control system of Claim 10, further comprising a satellite based video data transfer module.

16. The dual camera surveillance and control system of Claim 10, further comprising a housing ~~for the components~~ that is weather-tight.

17. The dual camera surveillance and control system of Claim 10, in which the energy

management module comprises a day/night sensor and a power select switch and in which the ambient energy charger is a solar panel that converts solar energy to electrical current, and further comprising:

- a) a communications board to intelligently capture desired relevant video data at a remote location for transmission to another location;
- b) an internet protocol module by which users ~~can~~ control the surveillance camera at a remote location;
- c) a satellite based video data transfer module;
- d) a housing ~~for the components~~ that is weather-tight.

18. The dual camera surveillance and control system of Claim 9, comprising:

- a) a power system having a battery, an energy management module, and an ambient energy charger for the battery, in which the energy management module comprises a day/night sensor, a low power detection module and a power select switch, and in which the ambient energy charger is a solar panel that converts solar energy to electrical current;
- b) a wireless transceiver for transmission of video to a base and for receiving instructions for the

*dual camera surveillance
and control*

system from the base;

c) a communications board to intelligently capture desired relevant video data at a remote location for transmission to another location;

d) an internet protocol module by which users ~~can~~ control the surveillance camera at a remote location over the internet;

e) a satellite based video data transfer module;

f) a housing ~~for the components~~ that is weather-tight.

19. The dual camera surveillance and control system of Claim 10, further comprising a housing ~~for the components~~ that is a weather-tight, substantially spherical dome having flat windows, the color camera and the mono camera mounted on a central axis within the sphere to allow pan and tilt rotation in full 360 degree rotation on two axes.

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.